



Portable Series



3LCD Technology



Hitachi Trade-Up Program



3 Year Warranty

HDMI HDMI



Closed Captioning

Key Features

- 3,200 ANSI Lumens
- Native XGA Resolution
- Hybrid 5,000 Hour Filter
- HDMI Input (HDCP Compliant)
- 4.96 Lb. Compact Design
- .5 Watt Power Consumption In Standby Saving Mode
- Auto Eco Mode
- Front Air Exhaust
- Soft Carry Case Included
- Audio Pass Through
- Audio Output
- Air Filter on Side and Lamp Door on Top for Easy Access
- Template Function
- Instant On/Off
- PIN Lock Security
- White Board/Blackboard Modes
- 30dB Eco Mode
- Blank/MyButton



Specifications

Model Name	CPX9
Liquid Crystal Panel Structure	0.63" polysilicon active-matrix TFT x 3
Number of Pixels	786,432 pixels
Resolution	540 TV lines
Video	1024 dots X 768 lines
RGB	16.7 million colors
Colors	Native 4:3/16:9 compatible
Aspect Ratio	Manual zoom / focus 1.2X (f=16.4~19.6mm)
Lens	1.3 - 1.5 : 1
Throw Ratio (distance : width)	200W UHP
Lamp	3,200 ANSI Lumens
Brightness	3,200 ANSI Lumens
Color Light Output	Approximately 3,000 hours (normal) 4,000 hours (Eco Mode)
Expected lamp Life**	500 : 1
Contrast Ratio	1W
Speaker Output	AC100 - 120V / AC220 - 240V 50/60 Hz
Power Supply	290W (0.5W @ standby in Power Saving Mode)
Power Consumption	5°C - 35°C (41°F - 95°F)
Operating Temperature	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, MAC 16"
Input Signals	Composite Video
RGB	Component Video
Acoustic Noise Level	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, PAL60
H-Sync	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
V-Sync	37 dB (30 dB in Eco Mode)
Vertical Keystone	15 k - 106 kHz
Approvals	50 Hz - 120 Hz
RGB Input	+ / - 30°
RGB Output	UL, C-UL, FCC, CE, RoHS
Digital Input	Analog RGB
Video Input	RGB
Audio	15pin Mini-Dsub x 1
Control Terminals	15pin Mini-Dsub x 1
Dimensions (W x D x H)	HDMI x 1 (HDCP Compliant)
Weight	Mini DIN 4-pin connector x 1
Additional Features	Composite Video
Supplied Accessories	Shared with RGB
Projector Part #	Input
Lamp Part #	Output
Remote Control Part #	9-pin D-sub connector x 1 (RS-232 control)
Filter Part #	12.0" x 8.7" x 3.0"
	4.96 lbs.
	My Screen, My Memory, My Button, My Text, My Source, Blackboard/Whiteboard Mode, Daytime Mode, Input Source Naming(English), Resolution Setting, Template, Closed Caption(for NTSC only), Audio Pass Through
	Remote Control, Batteries (AA), RGB cable, US Power Cord, Multiple Language Operator / Safety Manual, Security Label, Lens Cap, Soft Case
	CPX9
	CPX2020LAMP (DT01141)
	HLO2771
	UX36761



Aspect Ratio 4:3

Screen Size*		Throw Distance*	
Diagonal*	Width*	Min*	Max*
30	24	29	35
60	48	60	72
80	64	80	97
100	80	101	121
120	96	121	146
150	120	152	183
200	160	203	244
300	240	305	367

Throw Ratio: 1.3 - 1.5:1 (distance : width)


*Measured in inches

Disclaimer: Please use this throw distance calculator for reference purpose only. For permanent installation purpose, we recommended that you assume 10% calculation margin of error or to test the unit on site.

** Actual lamp life will vary by individual lamp and based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.

* Actual filter life will vary by individual filter and based on environmental conditions, selected operating mode, user settings and usage. Hours of average filter life specified are not guaranteed and do not constitute part of the product warranty.

For sales information, please call 800.225.1741
Printed 12.10



All specifications subject to change without notice.
3LCD and the 3LCD logo are registered trademarks of the Seiko Epson Corporation.
©2010 Hitachi America, Ltd. All Rights Reserved.